PL2559

REMO SUPER
ISO SUPER ROWING

ESPECIFICACIONES TÉCNICAS
TECHNICAL SPECIFICATIONS

- Fabricada en tubo cuadrado de acero Q235 de 3 mm de espesor.
- Estructura con pintura en polvo para una fijación total y una alta resistencia.
- Biomecánica de máquina diseñada especialmente para permitir la accesibilidad a cualquier tipo de usuario.
- Cuenta con asiento regulable en altura.
- Tapizado de asientos y respaldo con relleno de PU, antibacteriano e ignífugo.
- Rodamientos industriales y tornillería de alta calidad.
- 2 portadiscos de carga en acero inoxidable.
- Agarres cómodos recubiertos de goma no porosa. Ofrecen una muy buena sensación de agarre y seguridad al contacto.
- Tacos de PVC blandos antideslizantes en su base.

- Made of 3 mm thick Q235 steel square tube.
- Powder-coated structure for total fixation and high resistance.
- Machine biomechanics specially designed to allow accessibility to any type of user.
- It has a height-adjustable seat.
- Upholstered with PU and cotton filling, antibacterial and fire retardant.
- Industrial bearings and high quality screws.
- 2 stainless steel loading disc holders.
- Non-porous rubber coated comfort grips. They offer a very good feeling of grip and security upon contact.
- Soft non-slip PVC studs on the base.

DIMENSIONES Y PESO
SIZE AND WEIGHT

Medidas / Set up size:
149 x 143 x 138 cm.

Carga máxima / Maximum load:
250 kg. (125 kg por cada lado / on each side**)**

Peso / Net weight:
120 kg.