

PL2562



PRESS TRAS NUCA ISO INCLINE SHOULDER PRESS



ESPECIFICACIONES TÉCNICAS TECHNICAL SPECIFICATIONS

- Fabricada en tubo cuadrado de acero Q235 de 3 mm de espesor.
- Estructura con pintura en polvo para una fijación total y una alta resistencia.
- Biomecánica de máquina diseñada especialmente para permitir la accesibilidad a cualquier tipo de usuario.
- Cuenta con asiento regulable en altura.
- Tapizado de asientos y respaldo con relleno de PU, antibacteriano e ignífugo.
- Rodamientos industriales y tornillería de alta calidad.
- 8 portadiscos de carga en acero inoxidable.
- Agarres cómodos recubiertos de goma no porosa. Ofrecen una muy buena sensación de agarre y seguridad al contacto.
- Tacos de PVC blandos antideslizantes en su base.
- Made of 3 mm thick Q235 steel square tube.
- Powder-coated structure for total fixation and high resistance.
- Machine biomechanics specially designed to allow accessibility to any type of user.
- It has a height-adjustable seat.
- Upholstered with PU and cotton filling, antibacterial and fire retardant.
- Industrial bearings and high quality screws.
- 8 stainless steel loading disc holders.
- Non-porous rubber coated comfort grips. They offer a very good feeling of grip and security upon contact.
- Soft non-slip PVC studs on the base.

DIMENSIONES Y PESO SIZE AND WEIGHT



Medidas / Set up size:
141 x 186 x 189 cm.



Carga máxima / Maximum load:
250 kg. (125 kg por cada lado / on each side)



Peso / Net weight:
145 kg.